



EXPANDABLE BASE WITH NOISE FILTRATION/SURGE PROTECTION

- Four AC Outlets with Transformer Spacing
- Accepts Add-on Signal Line Modules to Accommodate System Expansion

AC Power

UL 1449 Suppression Rating	500V
Thermal Fusing	Yes
Single Pulse Energy Dissipation	1650 Joules
Response Time	< 1ns
Protection Modes	L-N, L-G, N-G
Protect or Disconnect™ Circuitry	Yes
Power Cord	8 ft fixed
Plug Type	right angle, 45 degree offset
Peak Impulse Current	52,000 Amps
Patented Power Management Circuit	Yes
Maximum Current Rating	15 A (1800W)
Line Voltage	120VAC, 50/60Hz
Initial Clamping Level	200V Peak, 141V RMS
EMI/RFI Noise Filtration	50 dB(100 KHz - 1MHz)
Auto-resetting Under-voltage shutoff	90V ± 6V
Auto-resetting Over-voltage shutoff	144V ± 8V

\$5,000,000 LIFETIME LIMITED CONNECTED EQUIPMENT PROTECTION POLICY
Go to: www.Panamax.com for details. 1.800.472.5555 Customer Relations

LIFETIME LIMITED PRODUCT WARRANTY

Panamax warrants to the purchaser of any standard Panamax surge protector that the surge protector shall be free of defects in design, material, or workmanship, and Panamax will repair or replace any defective unit.